Data sheet

HP Thunderbolt Dock G2





Turn heads and change minds with a stylish, modern expansion solution

Reinvent docking and boost productivity with the world's most versatile ThunderboltTM dock¹ the small, sophisticated HP Thunderbolt Dock G2. Designed for workspace flexibility and network manageability², it delivers USB-C^{TM3} device connectivity and optional integrated audio.⁴

Command your workspace from just one USB-C™ connection

Connect a single USB-C™ cable to your notebook³ to access a wired network, data, video, and charqing⁵ with a dock that supports both HP and non-HP Thunderbolt™ and USB-C™ notebooks.³

Reset your perception

Reclaim your work area with this space-saving centerpiece that helps create a clean desk. Its elegant, black, rounded design with smooth accents changes everything you thought you knew about docks.

Manage your enterprise fleet like a boss

Help IT easily secure and remotely manage⁶ a wide range of HP notebooks and the dock with advanced network manageability features² built into the dock, including WoL and MAC Address Pass Through in all power states and PXE Boot.

Maximize your multi-tasking

See every color and detail of your projects with a superfast connection to dual external 4K displays⁶ as soon as you plug your notebook into the dock.

Lock it down

Secure the base dock to a desk, table or your notebook through the lock slot with an optional HP lock. 8

USB-C™ charging, video, and the ability to deliver power to notebooks that require up to 200W power as of January 17th, 2018.

2. Advanced manageability features such as WoL and MAC Address Pass-Through in all power states supported only on HP Pro x2 612 G2, HP EliteBook 1040 G4, HP EliteBook x360 1020, 1030 G2, 800 G5, 700 G5, 600 G4, 400 G5, and G4 HP Mobile Workstations as of January 17th. 2018.

1. Based on Thunderbolt™ docks that support

- 3. Notebooks must be able to support USB-C™ power, video, USB-C™, and Thunderbolt™ industry standards.
- 4. HP Thunderbolt Dock Audio Module sold separately and required for audio.
- 5. USB-C™ notebook charging up to 100 watts supported through single USB-C™ cable. Combo cable, included on select models or sold separately, required to support both notebooks up to 100W and mobile workstations up to 200 watts.
- 6. Internet access required and sold separately.
- 7. Displays sold separately.
- 8. Lock sold separately.

Specifications



HP Thunderbolt Dock G2

Part number	HP Thunderbolt Dock 120W G2 2UK37AA/2UK37UT/2UK37ET HP Thunderbolt Dock 230W G2 2UK38AA/2UK38UT/2UK38ET (not available in the US) HP Thunderbolt Dock G2 w/ Combo Cable 3TR87AA/3TR87UT/3TR87ET	
Dimensions (H x W x D)	3.9 x 3.9 x 2.7 in (98 x 98 x 69 mm)	
Weight	1.76 lbs (0.8 kg)	
Compatibility	Tested and supported on select HP commercial notebooks. For HP notebook compatibility please visit - https://pcb.inc.hp.com/webapp/#!/us-en and search by notebook. Tested and supported on the following 3rd party notebooks: Apple MacBook Pro 16 2020 (Intel Coffee Lake), Apple MacBook Air 2020 (Intel Ice Lake), Apple MacBook Pro 13 2020 (M1 chip), Apple MacBook Air 13 2020 (M1 chip), Dell 5300 Chrome Enterprise 2020 (Whiskey Lake), Dell Latitude 5400 2020 (Whiskey Lake), Dell Latitude 7400 2020 (Whiskey Lake), Dell Latitude 7420 2021 (Tiger Lake-U), Lenovo Thinkbook 14 2020 (Ice Lake), Lenovo T14 2020 (AMD Renoir), and Lenovo X1 Carbon G8 Thinkpad 2020 (Whiskey Lake).	
Top components	LED and power button to power or wake host system ¹	
Front components	1 x USB-C® 3.2 Gen 2 port with data and power out (15W) 1 x USB-C® cable to connect to host system (0.7meter cable length)	
Side components	1 x USB-A 3.0 Gen 1 charging port 1 x Combo audio Jack 1 x Standard lock slot	
Back components	1 x Thunderbolt™ port 1 x USB-C® 3.2 Gen 2 port with DisplayPort™ 1.4 data and power out (15W) 2 x DisplayPort™ 1.4 ports 1 x VGA port 2 x USB-A 3.0 Gen 1 ports 1 x RJ45 port 1 x AC adapter connector (7.4mm)	
Network manageability features	PXE Boot Wake on LAN (from the Off, Sleep or Hibernation States²) MAC Address Pass Through (from the On, Off, Sleep or Hibernation States³) WLAN-LAN Switching ⁴	
External monitor support	For hosts that support DisplayPort 1.4 with Display Stream Compression: 3x FHD @ 60 Hz 3x QHD @ 60 Hz 3x 4K @ 60 Hz	
	For hosts that support DisplayPort 1.3/1.4: 3x FHD @ 60 Hz 3x QHD @ 60 Hz 1x 4K @ 60Hz	
	For hosts that support DisplayPort 1.2: 3x FHD @ 60 Hz 2x QHD @ 60 Hz 1x 4K @ 60Hz	
Power delivery (PD) profiles	PD 3.0: 5V/5A, 9V/5A, 12V/5A, 15V/5A, 20V/5A	
Networking	Supports 1 Gb of Ethernet	
Power to system	Up to 100W via USB-C [®] . Up to 75W on non HP machines. For HP ZBooks that require more than 100W power delivery should use the 3TR87AA HP Thunderbolt Dock 230W for 200W of power delivery.	
Operating voltage and current	19.7 V dc @ 6.1 A – 120W 19.7 V dc @ 11.8 A – 230W	
Temperature (operating)	0° C to 35° C (32° F to 95° F)	
Relative humidity noncondensing (operating)	10 % to 90 %	

- 1. The dock power button is not functional when connected to non-supported HP notebooks or non-HP notebooks.
- $2. \ Your \ computer \ might \ support \ Wake \ on \ LAN \ from \ the \ Off, \ Sleep. \ or \ Hibernate \ States, \ or \ only \ when \ the \ computer \ is \ On \ or \ in \ Sleep.$
- $3. \ Your computer might support MAC \ Address \ Pass \ Through \ the \ On, \ Off, \ Sleep \ or \ Hibernate \ States, \ or \ only \ when \ the \ computer \ is \ On \ or \ in \ Sleep.$
- $4.\,WLAN-LAN\,switching\,is\,supported\,only\,on\,select\,computers\,running\,Windows\,10\,operating\,system.$



Specifications

HP Thunderbolt Dock G2 Video resolution specifications

HP Thunderbolt Dock G2 video resolution specifications when the dock is connected to a Thunderbolt™ system:

lost specification	# of displays	Resolution	Supported configuration
DP 1.2 Thunderbolt™ host:			
HP Elite X2 1012 G1 HP EliteBook Folio G1	1	(1) 4096x2160 @ 60Hz	(1) DP or (1) TB or (1) USB-C™ Alt Mode
HP EliteBook X360 1020 & 1030 G2 HP EliteBook 1040 G4	2	(2) 4096 x 2160 @ 60Hz	(1) DP + 1 TB port or (1) USB-C™ Alt Mode port + 1 TB port
HP EliteBook 800 G5 ZBook 14u/15u G5	3	(1) 4096 x 2160 @ 60Hz + (2) 2560 x 1440 @ 60Hz	(1) 4096 x 2160 @ 60Hz from TB port (2) 2560x1440 @ 60Hz from DP ports or DP + USB-C™ Alt Mode
ZBooks 17, 15, Studio G3, G4	4	(1) 4096 × 2160 @ 60Hz +	(1) 4096 x 2160 @ 60Hz from TB port
		(2) 2560 x 1440 @ 60Hz+	(2) 2560x1440 @ 60Hz from DP ports or DP + USB-C [™] Alt Mode
		(1) 1920 x 1080 @ 60Hz	(1) 1920 x 1080 @ 60Hz from DP or USB-C [™] Alt Mode
lost specification	# of displays	Resolution	Supported configuration
DP 1.3 Thunderbolt™ host:	1	(1) 5120 × 2880 @ 60Hz	(1) DP or (1) TB or (1) USB-C™ Alt Mode

nost specification	# 01 displays	Resolution	Supported Configuration
DP 1.3 Thunderbolt™ host:			
	1	(1) 5120 × 2880 @ 60Hz	(1) DP or
			(1) TB or
			(1) USB-C™ Alt Mode
	2	(2) 4096 x 2160 @ 60Hz	(1) DP + 1 TB port or
			(1) USB-C™ Alt Mode + 1 TB port
	2	(2) 3840 x 2160 @ 60Hz +	(2) DP ports or
	_	(2,30.10 % 2.100 @ 00.12	(1) DP + 1 USB-C™ Alt Mode port or
			(1) DP + 1 TB port or
			(1) TB + 1 USB-C™ Alt Mode
	3	(2) 3840 x 2160 @ 60Hz +	(2) 3840 x 2160@60Hz from DP ports or DP + USB-C™ Alt Mode
	J	(1) 1920 x 12000 @ 60Hz	(1) 1920x1200 @ 60Hz from TB port
		(3) 2560 x 1600 @ 60hz	(2) DP ports + USB-C™ Alt Mode
	3	_	·
		(1) 3840 x 2160 @ 60Hz +	(1) 3840x2160 @ 60Hz from DP or USB-C™ Alt Mode
	4	(2) 2560 x 1440 @ 60Hz+	(2) 2560x1440 @ 60Hz from DP ports or DP + USB-C™ Alt Mode
		(1)1920 x 1200 @ 60Hz	(1) 1920 x 1200@ 60Hz from TB port

NOTE: Chart is based on 8bit DP1.2 displays (except for 5120x2880 single cable display). NOTE: with a DP1.3 Thunderbolt™ host, when 3 or more displays are attached, the Thunderbolt™ port is limited to a 1920x1200 @ 60hz DP1.2 display, or a 2560x1440@60hz DP1.3 display.



Specifications

HP Thunderbolt Dock G2 Video resolution specifications

HP Thunderbolt Dock G2 video resolution specifications when the dock is connected to a USB-C[™] Alt-Mode system⁵:

ost specification	# of displays	Resolution
DP 1.2 USB-C™ Host:		
HP EliteBook 840r G4	1	2560x1440 @ 60Hz
HP ProBook 600 G4, 400 G5	2	1920x1200 @ 60Hz
HP Pro x2 612 G2	3	(1) 1920×1200 @ 60Hz (2) 1280×768 @ 60Hz
DP 1.3 USB-C™ Host:		
HP EliteBook 700 G5	1	3840x2160 @ 60Hz
HP ProBook 645 G4	2 3	2560x1600 @ 60Hz+ (1) 2560x1600 @ 60Hz
HP ProBook 455 G5	4	(2) 1680×1050 @ 60Hz 1680 x 1050 @ 60Hz (requires MST)

^{5.} USB-C[™] systems will perform at USB 3.0 Gen1 speeds

HP Thunderbolt Dock G2 and cables compatibility

HP Thunderbolt Dock 120W G2 (2UK37AA)	HP Elite x2 1012 G1	
HP Thunderbolt Dock 120W G2 cable (3XB94AA)	HP Pro x2 612 G2	
	HP EliteBook Folio G1	
	HP EliteBook x360 1030 & 1020 G2	
	HP EliteBook 1040 G4	
	HP EliteBook 800, 700 G5	
	HP ProBook 600 G4, 400 G5	
	ZBook 14u/15u G5	
HP Thunderbolt Dock 230W G2 (2UK38AA)	HP ZBook 17, 15: G3, G4, G5 and Studio: G3, G4, G5	
HP Thunderbolt Dock 230W G2 cable (3XB95AA)	HP ZBook x2 G4	
	HP ZBook Studio x360 G5	
	HP ZBook 14u/15u G5	
	HP Zbook 15v G5	
	HP EliteBook 800, 700 G5, 1050 G1	
HP Thunderbolt Dock G2 w/ combo cable (3TR87AA) HP Thunderbolt Dock G2 combo cable (3XB96AA)	Compatible with all notebooks listed for 120W and 230W models	
	NOTE: Requires 230W AC adapter	

Sign up for updates hp.com/go/getupdated





Share with colleagues

Rate this document

© Copyright 2023 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. Thunderbolt™ is a trademark of Intel Corporation in the U.S. and other countries.



Thunderbolt[™] port will function as a USB 2.0 port with only data and power out (15W); no video.